



BENEFITS

Swiftspace is designed for flexibility, productivity, reducing costs, saving time and removing pain-points.



No loose parts to manage.



Minimal tools required.



No installers needed - it's DIY easy.



Reduce costs.



Installs in minutes, not hours

ſ	<u>–Ľ</u>

No punch list saves time.



Scope of Product

Strata is a straight, single configuration available in various combinations of wall heights and lengths. It is non-folding, but fits through standard doorways. Walls have aluminum frames with various upper panel options. Strata is a mobile solution with casters that swivel and lock, with optional caster covers. Integrated storage is available, and so are power/data trough add-ons.


Breadth of Offering

- Strata comes in standard lengths of 48 (1219mm), 60 (1524mm), 66 (1676mm) and 72 (1829mm) inches. Custom lengths are available.
- Strata heights are: 41 (1041mm), 52 (1321mm) and 66 (1676mm) inches.
- Strata stations are approximately 26" (660mm) deep overall with 24" (610mm) deep worksurfaces
- Worksurfaces can be height adjustable with a range of 21.9"-48.1" (556mm 1222mm) powered by a bluetooth controller or can be fixed height (set at 29"H (737mm) standard or custom height if requested).
- Upper panel inserts include semi-clear poly, laminate, whiteboard, magnetic whiteboard, fabric tackboards, Ezo sound-dampening panels, and acrylic (clear, frosted and printed).
- Accessories include but are not limited to; accessory rails with paper trays, pen holders and binder holders as well as monitor arms, CPU holders, keyboard arms and transaction countertops.
- For additional height and privacy requirements, panel extenders can be added. Panel extender come in acrylic, Ezo or laminate finishes.
- Storage options include but are not limited to; hanging Box/File pedestals, overheads (66"H (1676mm) only), freestanding pedestals, mounted storage and towers.

System Engineering

- Other than freestanding storage and clip on accessories, **all component parts are fully assembled at the factory into the workstation.***
- Strata is equipped with heavy-duty steel ball bearing casters with rubber wheels that are designed or go over thresholds, dockplates and other rough terrain without damage. *
- As a single surface station, Strata is designed to fit through doorways and so does not fold up. *





Construction

- Strata is constructed using 1.6" (40.64mm) lightweight, clear-anodized aluminum frame.
- Worksurfaces are 1" (25.4mm) thick high pressure laminate with a 45lb density particleboard core, .08" (2.032mm) edging. Options for powdercoated, thermoformed, and solid surface available upon request.
- All worksurfaces have a recess at the back along with a centered grommet to allow for ease of running cables and cords and attaching some accessories such as surface-mounted monitor arms.
- Castors are 2.5" (63.5mm) in diameter with grey non-marking rubber wheels that swivel and lock. They can be removed and replaced with adjustable glides that have 1" (25.4mm) of height adjustment for surface leveling on uneven floors.

Installation and Warranty

- Can be installed or serviced directly by the user or any common furniture installer and not violate or void any product warranty. Installation will not require any tools or professional training.
- Station ships fully assembled on casters; the entire station will be one unit with no separate pieces, except for any mobile storage or some accessories that are to be attached after installation.*
- For product warranty please see Conditions of Sale, Return Policy, and Warranty in the Specification and Price Guide

Electrical

- A power/data rail can be added to the bottom of the station. If this is done, the lower side panels are shortened to allow for a continuous run of power/data stations when stations are side-by-side.
- The power/data rail has 2 channels; the top channel is used to run power cables or hardwired power while the bottom (metallically separated from the top) can support up to 40 CAT6 data cables or phone lines.
- Power can be handled on an individual station basis using a detachable powerbar with a 15ft power cord.

